



THICK STRIP

DESCRIPTION

THICK-STRIP is a gel-solvent based, water clean-up stripper specifically designed for stripping acrylic sealers on most concrete and masonry surfaces.

THICK-STRIP is suitable for stripping hydrocarbon curing compounds in vertical and overhead situations (bridge escarpments etc.) due to its higher viscosity.

THICK-STRIP is suitable for use on most paint systems, except for 2pack epoxies, and urethanes.

THICK-STRIP contains selected ingredients to emulsify the sealer with water, allowing a water wash off.

DIRECTIONS

Apply onto sealer surface ; can be shear thinned, sprayed then recover to hang up on vertical & overhead surfaces or applied by brush .

Allow it to soften film.

When sealer has a started to bubble and changes appearance to a slightly milky appearance, scrape or waterblast off.

Allow dry.

Repeat applications may be necessary for any remaining sealer.

FIRST AID, SAFETY & STORAGE

Refer to Material Safety Data sheet. These are available on request.

PACKS

4L, 10L, 20L, 200L.

COLORO THICK STRIP - PDS JAN 2021

This Product Data Sheet (PDS) summarises our best knowledge of the product, including how to use and apply the product based on the information available at the time. You should read this PDS carefully and consider the information in the context of how the product will be used, including in conjunction with any other product and the type of surfaces to, and the manner in which, the product will be applied. Our responsibility for products sold is subject to our standard terms and conditions of sale. Chemical House does not accept any liability either directly or indirectly for any losses suffered in connection with the use or application of the product whether in accordance with any advice, specification, recommendation, or information given by it.

CHEMICAL HOUSE

Headquarters

9 Production Avenue, Molendinar

Queensland, 4214 Australia

Ph: +61 7 5594 0344

www.chemicalhouse.com.au

