CHEMICAL HOUSE ®

ACN 010418 569

9 Production Avenue Molendinar. Qld 4214

PO BOX 595 ASHMORE CITY, QLD. 4214

"from our bouse to yours" ®

LTD

PRODUCT:

CONCRETOR'S MATE 24% 7 - DAY HARDSEAL

DESCRIPTION:

CONCRETOR'S MATE ACRYLIC HARD SEALER is a 7 DAY solvent based sealer system designed to be used on Stencil, Stamped Concrete, Garden Edging, Exposed Aggregate etc. CONCRETOR'S MATE HARD SEAL should be applied to the surface with a low pressure spray or natural hair hair broom, use of nylon, polyethylene or other plastics will result in their dissolution.

DIRECTIONS FOR USE:

Do not apply in temperatures below 5degC. or above 30deg C. Apply with a Spray/broom at the rate of 2-5m2/Litre. Do NOT apply on wet concrete WAIT until the concrete has cured OR apply over 1 coat of same day sealer, 7-14 days after the 1st coat. Do NOT use on glazed or semiglazed tiles without special preparation. Apply 1-3 coats. Application of each subsequent coat should be at right angles to the previous. Apply a third coat if gloss level not high enough.

FIRST AID:

If poisoning occurs, contact a doctor or Poisons Information Centre. If swallowed, do NOT induce vomiting. If in eyes, hold eyes open. flood with water for at least 15 minutes and see a doctor. If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water.

RISK PHRASES
SAFETY PHRASES

RIO Flammable. R20/21: Harmful by inhålation and if swallowed. R38: Irritating to skin.

SAFETY PHRASES

/S16: Keep away from sources of ignition - No Smoking. S25: Avoid contact with eyes. S29: Do not empty into drains.

COVERAGE:

2-5m2/Litre/

CLEAN UP:

Wash up with Xylene

STORAGE:

Product is Class 3 Dangerous Good & should be stored as specified in AS1940. Keep in a cool dry place, away from ignition sources and away from incompatible chemicals.

PACKS:

-20L,/200L.

Ref:EP4010-03_HardSeal_pds.doe Date:July 08