



## UVA32 ONECOAT SEALER

**DESCRIPTION** UVA32 ONECOAT SEALER is a solvent-based sealer system designed to be used on broomed concrete, stenciled concrete, stamped concrete, Garden Edging, Exposed Aggregate etc.

COLORO UVA32 ONECOAT SEALER should be applied to the surface with a low-pressure spray, broom, or roller, use of nylon, polyethylene or other plastics will result in their dissolution.

**DIRECTIONS FOR USE** Do not apply in temperatures below 5degC. or above 30deg C.

Apply with a Spray, Broom or Roller at the rate of 2-5m<sup>2</sup>/Litre.

Do NOT apply on wet concrete WAIT until the concrete has cured.

The product can be applied as early as 7 days IF applied over 1 coat of same day sealer (i.e. Cure and seal) applied 7 days earlier.

Otherwise if applying neat to the fresh concrete without a cure and seal style primer, the concrete must be at least 28 days old prior to application.

Do NOT use on glazed or semi glazed tiles without special preparation.

Though the product is designed as a single coat, if additional film build or highly gloss levels are required, additional coats can be added.

Application of each subsequent coat should be at right angles to the previous.

**FIRST AID** If poisoning occurs, contact a doctor or Poisons Information Centre.

If swallowed, do NOT induce vomiting. If in eyes, hold eyes open. flood with water for at least 15 minutes and see a doctor.

If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water.

### APPLICATION RATE

2-5m<sup>2</sup>/Litre

### CLEAN UP

Wash up with Xylene

### STORAGE

Product is Class 3 Dangerous Good & should be stored as specified in AS1940.

Keep in a cool dry place, away from ignition sources and away from incompatible chemicals.

### PACKS

20L, 200L, 1,000L.

### COLORO UVA32 OneCoat - PDS July 2020

This Product Data Sheet (PDS) summarises our best knowledge of the product, including how to use and apply the product based on the information available at the time. You should read this PDS carefully and consider the information in the context of how the product will be used, including in conjunction with any other product and the type of surfaces to, and the manner in which, the product will be applied. Our responsibility for products sold is subject to our standard terms and conditions of sale. Chemical House does not accept any liability either directly or indirectly for any losses suffered in connection with the use or application of the product whether in accordance with any advice, specification, recommendation, or information given by it.

### CHEMICAL HOUSE

#### Headquarters

9 Production Avenue, Molendinar

Queensland, 4214 Australia

Ph: +61 7 5594 0344

[www.chemicalhouse.com.au](http://www.chemicalhouse.com.au)

